

## [2017 New 300-206 New Questions Free Download In Lead2pass (151-175)]

2017 August Cisco Official New Released 300-206 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! 2017 get prepared with fully updated Cisco 300-206 real exam questions and accurate answers for 300-206 exam. Lead2pass IT experts review the 300-206 newly added questions and offer correct Cisco 300-206 exam questions answers. 100% pass easily! Following questions and answers are all new published by Cisco Official Exam Center: <https://www.lead2pass.com/300-206.html>

QUESTION 151 Which two TCP ports must be open on the Cisco Security Manager server to allow the server to communicate with the Cisco Security Manager client? (Choose two.) A. 1741 B. 443 C. 80 D. 1740 E. 8080 Answer: AB

QUESTION 152 Which command enables the HTTP server daemon for Cisco ASDM access? A. http server enable B. http server enable 443 C. crypto key generate rsa modulus 1024 D. no http server enable Answer: A

QUESTION 153 Which function in the Cisco ASDM ACL Manager pane allows an administrator to search for a specific element? A. Find B. Device Management C. Search D. Device Setup Answer: A

QUESTION 154 Which two router commands enable NetFlow on an interface? (Choose two.) A. ip flow ingress B. ip flow egress C. ip route-cache flow infer-fields D. ip flow ingress infer-fields E. ip flow-export version 9 Answer: AB

QUESTION 155 Refer to the exhibit. Which two statements about the SNMP configuration are true? (Choose two.) A. The router's IP address is 192.168.1.1 B. The SNMP server's IP address is 192.168.1.1 C. Only the local SNMP engine is configured. D. Both the local and remote SNMP engines are configured. E. The router is connected to the SNMP server via port 162. Answer: BD

QUESTION 156 To which port does a firewall send secure logging messages? A. TCP/1500 B. UDP/1500 C. TCP/500 D. UDP/500 Answer: A

QUESTION 157 What is a required attribute to configure NTP authentication on a Cisco ASA? A. Key ID B. IPsec C. AAA D. IKEv2 Answer: A

QUESTION 158 Which function does DNSSEC provide in a DNS infrastructure? A. It authenticates stored information. B. It authorizes stored information. C. It encrypts stored information. D. It logs stored security information. Answer: A

QUESTION 159 Refer to the exhibit. Which two statements about this firewall output are true? (Choose two.) A. The output is from a packet tracer debug. B. All packets are allowed to 192.168.1.0 255.255.0.0. C. All packets are allowed to 192.168.1.0 255.255.255.0. D. All packets are denied. E. The output is from a debug all command. Answer: AC

QUESTION 160 Which utility can you use to troubleshoot and determine the timeline of packet changes in a data path within a Cisco firewall? A. packet tracer B. ping C. traceroute D. SNMP walk Answer: A

QUESTION 161 What can an administrator do to simultaneously capture and trace packets in a Cisco ASA? A. Install a Cisco ASA virtual appliance. B. Use the trace option of the capture command. C. Use the trace option of the packet-tracer command. D. Install a switch with a code that supports capturing, and configure a trunk to the Cisco ASA. Answer: B

QUESTION 162 Refer to the exhibit. Which command can produce this packet tracer output on a firewall? A. packet-tracer input INSIDE tcp 192.168.1.100 88 192.168.2.200 3028 B. packet-tracer output INSIDE tcp 192.168.1.100 88 192.168.2.200 3028 C. packet-tracer input INSIDE tcp 192.168.2.200 3028 192.168.1.100 88 D. packet-tracer output INSIDE tcp 192.168.2.200 3028 192.168.1.100 88 Answer: A

QUESTION 163 At which firewall severity level will debugs appear on a Cisco ASA? A. 7 B. 6 C. 5 D. 4 Answer: A

QUESTION 164 A Cisco ASA is configured in multiple context mode and has two user-defined contexts--Context\_A and Context\_B. From which context are device logging messages sent? A. Admin B. Context\_AC. Context\_BD. System Answer: A

QUESTION 165 Which three statements about the software requirements for a firewall failover configuration are true? (Choose three.) A. The firewalls must be in the same operating mode. B. The firewalls must have the same major and minor software version. C. The firewalls must be in the same context mode. D. The firewalls must have the same major software version but can have different minor versions. E. The firewalls can be in different context modes. F. The firewalls can have different Cisco AnyConnect images. Answer: ABC

QUESTION 166 What can you do to enable inter-interface firewall communication for traffic that flows between two interfaces of the same security level? A. Run the command same-security-traffic permit inter-interface globally. B. Run the command same-security-traffic permit intra-interface globally. C. Configure both interfaces to have the same security level. D. Run the command same-security-traffic permit inter-interface on the interface with the highest security level. Answer: A

QUESTION 167 How many bridge groups are supported on a firewall that operate in transparent mode? A. 8 B. 16 C. 10 D. 6 Answer: A

QUESTION 168 In which way are management packets classified on a firewall that operates in multiple context mode? A. by their interface IP address B. by the routing table C. by NAT D. by their MAC addresses Answer: A

QUESTION 169 Where on a firewall does an administrator assign interfaces to contexts? A. in the system execution space B. in the admin context C. in a user-defined context D. in the console Answer: A

QUESTION 170 Which kind of Layer 2 attack targets the STP root bridge election process and allows an attacker to control the flow of traffic? A. man-in-the-middle B. denial of service C. distributed denial of service D. CAM overflow Answer: A

QUESTION 171 Which Layer 2 security feature validates ARP packets? A. DAIB. DHCP server C. BPDU guard D. BPDU filtering Answer: A

QUESTION 172 If you disable PortFast on switch ports that are connected to a Cisco

ASA and globally turn on BPDU filtering, what is the effect on the switch ports? A. The switch ports are prevented from going into an err-disable state if a BPDU is received. B. The switch ports are prevented from going into an err-disable state if a BPDU is sent. C. The switch ports are prevented from going into an err-disable state if a BPDU is received and sent. D. The switch ports are prevented from forming a trunk. Answer: C QUESTION 173 In a Cisco ASAv failover deployment, which interface is preconfigured as the failover interface? A. GigabitEthernet0/2 B. GigabitEthernet0/4 C. GigabitEthernet0/6 D. GigabitEthernet0/8 Answer: D QUESTION 174 What are the three types of private VLAN ports? (Choose three.) A. promiscuous B. isolated C. community D. primary E. secondary F. trunk Answer: ABC QUESTION 175 Which VTP mode supports private VLANs on a switch? A. transparent B. server C. client D. off Answer: A Latest 300-206 questions and answers from Cisco Exam Center offered by Lead2pass for free share now! Read and remember all real questions answers, Guarantee pass 300-206 real test 100% or full money back! 300-206 new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDQ3hFS2lmMTdVb3c> 2017 Cisco 300-206 exam dumps (All 251 Q&As) from Lead2pass: <https://www.lead2pass.com/300-206.html> [100% Exam Pass Guaranteed]