

## [2017 New New Lead2pass Cisco 300-135 New Questions Free Download (16-30)]

[2017 July Cisco Official New Released 300-135 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed!](#) Are you worrying about the 300-135 exam? Lead2pass provides the latest 300-135 braindumps and guarantees you passing 300-135 exam beyond any doubt. Following questions and answers are all new published by Cisco Official Exam Center:

<http://www.lead2pass.com/300-135.html> QUESTION 16 Which two statements about the Cisco Aironet Desktop Utility (ADU) are true? (Select two) A. The Aironet Desktop Utility (ADU) profile manager feature can create and manage only one profile for the wireless client adapter. B. The Aironet Desktop Utility (ADU) can support only one wireless client adapter installed and used at a time. C. The Aironet Desktop Utility (ADU) can be used to establish the association between the client adapter and the access point, manage authentication to the wireless network, and enable encryption. D. The Aironet Desktop Utility (ADU) and the Microsoft Wireless Configuration Manager can be used at the same time to configure the wireless client adapter. Answer: BC

QUESTION 17 At which layer of the OSI model does the Spanning Tree Protocol (STP) operate at? A. Layer 5 B. Layer 4 C. Layer 3 D. Layer 2 E. Layer 1 Answer: D

QUESTION 18 In computer networking a multicast address is an identifier for a group of hosts that have joined a multicast group. Multicast addressing can be used in the Link Layer (OSI Layer 2), such as Ethernet Multicast, as well as at the Internet Layer (OSI Layer 3) as IPv4 or IPv6 Multicast. Which two descriptions are correct regarding multicast addressing? A. The first 23 bits of the multicast MAC address are 0x01-00-5E. This is a reserved value that indicates a multicast application. B. The last 3 bytes (24 bits) of the multicast MAC address are 0x01-00-5E. This is a reserved value that indicates a multicast application. C. To calculate the Layer 2 multicast address, the host maps the last 23 bits of the IP address into the last 24 bits of the MAC address. The high-order bit is set to 0. D. The first 3 bytes (24 bits) of the multicast MAC address are 0x01-00-5E. This is a reserved value that indicates a multicast application. Answer: CD

QUESTION 19 EIGRP is being used as the routing protocol on the Company network. While troubleshooting some network connectivity issues, you notice a large number of EIGRP SIA (Stuck in Active) messages. What causes these SIA routes? (Select two) A. The neighboring router stops receiving ACK packets from this router. B. The neighboring router starts receiving route updates from this router. C. The neighboring router is too busy to answer the query (generally caused by high CPU utilization). D. The neighboring router is having memory problems and cannot allocate the memory to process the query or build the reply packet. Answer: CD  
Explanation: SIA routes are due to the fact that reply packets are not received. This could be caused by a router which is unable to send reply packets. The router could have reached the limit of its capacity, or it could be malfunctioning. Notes: If a router does not receive a reply to all outstanding queries within 3 minutes, the route goes to the stuck in active (SIA) state. The router then resets the neighbors that fail to reply by going active on all routes known through that neighbor, and it re-advertises all routes to that neighbor.

<http://www.cisco.com/warp/public/103/eigrp3.html> QUESTION 20 You want to enhance the security within the Company LAN and prevent VLAN hopping. What two steps can be taken to help prevent this? (Select two) A. Enable BPD guard. B. Disable CDP on ports where it is not necessary. C. Place unused ports in a common unrouted VLAN. D. Prevent automatic trunk configuration. E. Implement port security. Answer: CD

QUESTION 21 The following commands are issued on a Cisco Router:

```
Router(configuration)#access-list 199 permit tcp host 10.1.1.1 host 172.16.1.1
Router(configuration)#access-list 199 permit tcp host 172.16.1.1 host 10.1.1.1
Router(configuration)#exit
Router#debug ip packet 199
```

What will the debug output on the console show? A. All IP packets passing through the router. B. Only IP packets with the source address of 10.1.1.1. C. All IP packets from 10.1.1.1 to 172.16.1.1. D. All IP Packets between 10.1.1.1 and 172.16.1.1. Answer: D  
Explanation: In this example, the "debug ip packet" command is tied to access list 199, specifying which IP packets should be debugged. Access list 199 contains two lines, one going from the host with IP address 10.1.1.1 to 172.16.1.1 and the other specifying all TCP packets from host 172.16.1.1 to 10.1.1.1.

QUESTION 22 What level of logging is enabled on a Router where the following logs are seen? %LINK-3-UPDOWN: Interface FastEthernet0/1, changed state to up %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up A. alerts B. critical C. errors D. notifications Answer: D  
Explanation: Cisco routers, switches, PIX and ASA firewalls prioritize log messages into 8 levels (0-7), as shown below:

Level	Name	Description
0	Emergencies	System is unusable
1	Alerts	Immediate action needed
2	Critical	Critical conditions
3	Errors	Error conditions
4	Warnings	Warning conditions
5	Notifications	Informational messages
6	Informational	Normal but significant conditions
7	Debugging	Debugging messages

When you enable logging for a specific level, all logs of that severity and greater (numerically less) will be logged. In this case we can see that logging level of 3 (as seen by the 3 in "LINK-3-UPDOWN") and level 5 (as seen by the 5 in "LINEPROTO-5-UPDOWN") are shown, which means that logging level 5 must have been configured. As shown by the table, logging level 5 is Notifications.

QUESTION 23 You have the following commands on your Cisco Router: ip ftp username admin ip ftp password backup You have been asked to switch from FTP to HTTP. Which two commands will you use to replace the existing commands? A. ip http username admin B.

ip http client username adminC. ip http password backupD. ip http client password backupE. ip http server username adminF.  
ip http server password backup Answer: BExplanation:Configuring the HTTP ClientPerform this task to enable the HTTP client  
and configure optional client characteristics. The standard HTTP 1.1 client and the secure HTTP client are always enabled. No  
commands exist to disable the HTTP client. For information about configuring optional characteristics for the HTTPS client, see the  
HTTPS-HTTP Server and Client with SSL 3.0, Release 12.2(15)T, feature module. SUMMARY STEPS1. enable2. configure  
terminal3. ip http client cache {ager interval minutes | memory {file file-size-limit | pool pool-size-limit}4. ip http client connection  
{forceclose | idle timeout seconds | retry count | timeout seconds}5. ip http client password password6. ip http client proxy-server  
proxy-name proxy-port port-number7. ip http client response timeout seconds8. ip http client source-interface type number9. ip http  
client username username Reference: HTTP 1.1 Web Server and Client.

[http://www.cisco.com/en/US/docs/ios/netmgmt/configuration/guide/nm\\_http\\_web.html](http://www.cisco.com/en/US/docs/ios/netmgmt/configuration/guide/nm_http_web.html) QUESTION 24You have 2 NTP servers in  
your network - 10.1.1.1 and 10.1.1.2. You want to configure a Cisco router to use 10.1.1.2 as its NTP server before falling back to  
10.1.1.1. Which commands will you use to configure the router? A. ntp server 10.1.1.1ntp server 10.1.1.2B. ntp server 10.1.1.1  
ntp server 10.1.1.2 primaryC. ntp server 10.1.1.1ntp server 10.1.1.2 preferD. ntp server 10.1.1.1 fallbackntp server 10.1.1.2  
Answer: CExplanation:A router can be configured to prefer an NTP source over another. A preferred server's responses are  
discarded only if they vary dramatically from the other time sources. Otherwise, the preferred server is used for synchronization  
without consideration of the other time sources. Preferred servers are usually specified when they are known to be extremely  
accurate. To specify a preferred server, use the prefer keyword appended to the ntp server command. The following example tells the  
router to prefer TimeServerOne over TimeServerTwo: Router#config terminalEnter configuration commands, one per line. End with  
CNTL/Z. Router(config)#ntp server TimeServerOne preferRouter(config)#ntp server TimeServerTwoRouter(config)#Z QUESTION  
25The following command is issued on a Cisco Router: Router(configuration)#logging console warnings Which alerts will be seen  
on the console? A. Warnings onlyB. debugging, informational, notifications, warningsC. warnings, errors, critical, alerts,  
emergenciesD. notifications, warnings, errorsE. warnings, errors, critical, alerts Answer: CExplanation:Cisco routers prioritize  
log messages into 8 levels (0-7), as shown below: LevelLevel NameDescription0 Emergencies System is unusable1 Alerts  
Immediate action needed2 Critical Critical conditions3 Errors Error conditions4 Warnings Warning conditions5 Notifications  
Informational messages6 Informational Normal but significant conditions7 Debugging Debugging messages When you enable  
logging for a specific level, all logs of that severity and greater (numerically less) will be logged. In this case, when you enable  
console logging of warning messages (level 4), it will log levels 0-4, making the correct answer warnings, errors, critical, alerts, and  
emergencies. QUESTION 26Which two of the following options are categories of Network Maintenance tasks? A. FirefightingB.  
Interrupt-drivenC. Policy-basedD. StructuredE. Foundational Answer: BDEExplanation:Proactive Versus Reactive Network  
Maintenance:Network maintenance tasks can be categorized as one of the following: Structured tasks: Performed as a predefined  
plan.Interrupt-driven tasks: Involve resolving issues as they are reported. QUESTION 27A customer network engineer has made  
configuration changes that have resulted in some loss of connectivity. You have been called in to evaluate a switch network and  
suggest resolutions to the problems. PC2 in VLAN 200 is unable to ping the gateway address 172.16.200.1; identify the issue. A.  
VTP domain name mismatch on SW4B. VLAN 200 not configured on SW1C. VLAN 200 not configured on SW2D. VLAN  
200 not configured on SW4 Answer: DExplanation:By looking at the configuration for SW4, we see that it is missing VLAN 200,  
and the "switchport access vlan 200" command is missing under interface eth 0/0: QUESTION 28A customer network engineer has  
made configuration changes that have resulted in some loss of connectivity. You have been called in to evaluate a switch network  
and suggest resolutions to the problems. Which of statement is true regarding STP issue identified with switches in the given  
topology? A. Loopguard configured on the New\_Switch places the ports in loop inconsistent stateB. Rootguard configured on  
SW1 places the ports in root inconsistent stateC. Bpduguard configured on the New\_Switch places the access ports in error-disable  
D. Rootguard configured on SW2 places the ports in root inconsistent state Answer: AExplanation:On the new switch, we see that  
loopguard has been configured with the "spanning-tree guard loop" command. The loop guard feature makes additional checks. If  
BPDUs are not received on a non-designated port, and loop guard is enabled, that port is moved into the STP loop- inconsistent  
blocking state, instead of the listening / learning / forwarding state. Without the loop guard feature, the port assumes the designated  
port role. The port moves to the STP forwarding state and creates a loop. QUESTION 29A customer network engineer has made  
configuration changes that have resulted in some loss of connectivity. You have been called in to evaluate a switch network and  
suggest resolutions to the problems. You have configured PVST+ load balancing between SW1 and the New\_Switch in such a way  
that both the links E2/2 and E2/3 are utilized for traffic flow, which component of the configuration is preventing PVST+ load  
balancing between SW1 and SW2 links A. Port priority configuration on SW1B. Port priority configuration on the New\_Switch  
C. Path cost configuration on SW1D. Path cost configuration on the New\_Switch Answer: DExplanation:Here is the

configuration found on the New\_Switch: This causes the port cost for link eth 1/3 to increase the path cost to 250 for all VLANs, making that link less preferred so that only eth 1/2 will be used. QUESTION 30A customer network engineer has made configuration changes that have resulted in some loss of connectivity. You have been called in to evaluate a switch network and suggest resolutions to the problems. Refer to the topology. SW1 Switch Management IP address is not pingable from SW4. What could be the issue? A. Management VLAN not allowed in the trunk links between SW1 and SW4B. Management VLAN not allowed in the trunk links between SW1 and SW2C. Management VLAN not allowed in the trunk link between SW2 and SW4D. Management VLAN ip address on SW4 is configured in wrong subnetE. Management VLAN interface is shutdown on SW4

Answer: D  
Explanation: In the network, VLAN 300 is called the Management VLAN. Based on the configurations shown below, SW1 has VLAN 300 configured with the IP address of 192.168.10.1/24, while on SW4 VLAN 300 has an IP address of 192.168.100.4/24, which is not in the same subnet. Lead2pass offers the latest 300-135 PDF and VCE dumps with new version VCE player for free download, and the new 300-135 dump ensures your exam 100% pass. 300-135 new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDRnY1enRHb3hVeDQ> 2017 Cisco 300-135 exam dumps (All 110 Q&As) from Lead2pass: <http://www.lead2pass.com/300-135.html> [100% Exam Pass Guaranteed]