

## [Lead2pass New 2017 Latest Lead2pass 400-101 Questions & Answers PDF Free Download (621-640)]

Lead2pass 2017 October New Cisco 400-101 Exam Dumps! 100% Free Download! 100% Pass Guaranteed! Since I recently passed the the Cisco 400-101 exam, it's time for me to share the Lead2pass exam dumps I used when preparing for this exam. Following questions and answers are all new published by Cisco Official Exam Center: <https://www.lead2pass.com/400-101.html>

QUESTION 621 What are three required attributes in a BGP update message? (select three) A. AGGREGATOR B. AS\_PATH C. ORIGIN D. MED E. NEXT\_HOP Answer: BCE

QUESTION 622 Refer to the exhibit. Which tag will be applied to 172.16.50.0/24 route? A. 10 B. 20 C. 11 D. 40 Answer: A

QUESTION 623 Which three types of Layer 2 isolation do private VLANs provide? (Choose three) A. Community B. Isolated C. Blocking D. Promiscuous E. Private group Answer: ABD

QUESTION 624 What are three core Features of GET VPN? (Choose three.) A. The rekey mechanism B. Time-based anti-replay C. AES D. MPLS E. Partial mesh F. Cooperative keys Answer: ABF

QUESTION 625 Refer to the exhibit. If R1 and R2 are on the same network, what is the effect on the network when you apply the given configuration to R1 and R2? A. A symmetric routing occurs because the bandwidth and delay K value settings are mismatched. B. The interface bandwidth and delay settings adjust automatically to match the new metric settings. C. The neighbor adjacency between R1 and R2 temporarily resets and then reestablishes itself. D. R1 and R2 fail to form a neighbor adjacency. Answer: D

QUESTION 626 Which IPv4 mitigation method allows IPv4-only devices to communicate with IPv6-only devices? A. GRE tunnel B. Dual stack C. ISA TAP tunnel D. NAT64 Answer: D

QUESTION 627 Which three components are in a MPLS header? A. A 4-bit experimental use field B. An 8-bit TTL C. A 4-bit label stack entry D. A 2-bit bottom of stack E. A 3-bit experimental use field F. A 20-bit label Answer: BEF

QUESTION 628 Which two statements about route distribution are true? (Choose two.) A. Redistributing the entire BGP table from the Internet works well when using multiple OSPF areas. B. IS-IS does not support Layer 2 routes that leak into a Layer 1 domain. C. Mutual redistribution at multiple points can create a routing loop. D. IBGP is used within the AS to carry EBGP attributes that otherwise would be lost if EBGP was redistributed into IGP. E. The unequal cost multipath load-balancing characteristic is lost when redistributing OSPF into EIGRP. Answer: CD

QUESTION 629 Which type of ACL can be applied only to Layer 2 ports? A. Reflexive ACLs B. VLAN ACLs C. Standard ACLs D. Port ACLs E. Dynamic ACLs Answer: D

QUESTION 630 Which action does route poisoning take that serves as a loop-prevention method? A. It prohibits a router from advertising back onto the interface from which it was learned. B. It advertises a route with an unreachable metric back onto the interface from which it was learned. C. It immediately sends routing updates with unreachable metric to all devices. D. It poisons the route by tagging it uniquely within the network. Answer: B

QUESTION 631 Which two values are required to implement an EIGRP named configuration? (Choose two.) A. Process-id B. Router-id C. Subnet-mask D. Address-family E. Virtual-instance-name Answer: DE

QUESTION 632 Which option describes how a VTPv3 device responds when it detects a VTPv2 device on a trunk port? A. It sends VTPv2 packets only. B. It sends a Special packet that contains VTPv3 and VTPv2 packets information. C. It sends VTPv3 packets only. D. It sends VTPv3 and VTPv2 packets. Answer: D

QUESTION 633 Which technology uses MPLS to provide IPv6 connectivity to customers in the core network without the need for dual stack? A. 6to4 B. NAT64 C. NAT D. SPE Answer: D

QUESTION 634 Which three statements about bridge assurance are true? A. Bridge assurance can be enabled on one end of a link or on the both ends. B. If a bridge assurance ports failed to receive a BPDU after a timeout, the port is put into an error disabled state. C. If a bridge assurance ports failed to receive a BPDU after a timeout, the port is put into a blocking state. D. Bridge assurance is enabled on STP multipoint links only. E. Bridge assurance must be enabled on both the ends of a link. F. Bridge assurance is enabled on STP point-to-point links only. Answer: CEF

QUESTION 635 What is the function of the rendezvous point in PIM? A. It redistributes the multicast configuration to its connected neighbor. B. It will redistribute the unicast routes to avoid an RPF failure. C. It is the main source of the multicast traffic. D. It acts as a shared root for a multicast tree. Answer: D

QUESTION 636 Refer to the exhibit. Which traffic gets set to AF41 by marking policy on interface GigabitEthernet0/0? A. Any traffic matching access-list tp-rooms and access-list stream in G. B. No Traffic gets set to AF41. C. Only traffic matching access-list tp-rooms. D. Only traffic matching access-list streaming. Answer: A

QUESTION 637 Which three actions are required when configuring NAT-PAT? (Choose three) A. Specify an IPv4-to-IPv6 translation. B. Enable NAT-PT globally. C. Specify a /96 prefix that will map to an IPv4 address. D. Specify a /48 prefix that will map to a MAC address. E. Specify a /32 prefix that will map to an IPv6 address. F. Specify an IPv6-to-IPv4 translation. Answer: ACF

QUESTION 638 Which two statements about HDLC operations in asynchronous balanced mode are true? (Choose two.) A. Either device can send frames at any time. B. Each device must negotiate with its neighbor before sending frames. C. Each device must negotiate with its neighbor to recover from framing errors. D. Either device can initiate transmission of frames. E. The initiating

device sends a DTE frame. Answer: CD QUESTION 639 Drag and Drop Question Drag each QoS application-traffic on the left to the matching definition on the right. Answer: QUESTION 640 Which prefix List Matches and permits all RFC 1918 network 10.0.0.0 routes that have subnet masks of /16 through /24? A. ip prefix-list foo seq 10 perm it 10.0.0.0/16 le 24. B. ip prefix-list foo seq 10 permit 10.0.0.0/16 ge 15 le 25. C. ip prefix-list foo seq 10 perm it 10.0.0.0/8 ge 15 le 25. D. ip prefix-list foo seq 10 permit 10.0.0.0/8 ge 16 le 25. Answer: D More free Lead2pass 400-101 exam new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDZ0lrZUFjNWtFYlk> I hope Lead2pass exam questions from the Cisco 400-101 exam helps you pass the exam and earn your Cisco certification! Happy Studying! 2017 Cisco 400-101 (All 969 Q&As) exam dumps (PDF&VCE) from Lead2pass: <https://www.lead2pass.com/400-101.html> [100% Exam Pass Guaranteed]